



don't save lamp, save energy, save our Earth

FALCON 2

Application

A new ultra compact flood light with the latest energy saving LED light source designed for both indoor and outdoor application such as :

- Billboards
- Landscape
- Loading Bays
- Signages
- Security Post
- Building Facade

Construction

The housing is made from die cast aluminium, chemically treated and coated with polyester powder coating for resistance to corrosion and saline environments.

Front tempered clear safety glass for maximum brightness.

Stainless steel fasteners provide additional protection against corrosion

Silicon gasket for maximum protection against ingress of water and dust.

Control gear and lamp are integral in the housing and PG 13.5 cable gland is provided.

Aluminium	LED	IP 65	CE
-----------	-----	-------	----



MODEL	DFSD-30	DFSD-50	DFS-80F	DFS-100F
Lamp	30W	50W	80W	100W
Luminous Flux (lm)	> 3000	> 5000	> 6400	> 8000
Beam Angle	120°			
Dimensions (L x W x T)	200 x 160 x 55	240 x 180 x 55	290 x 250 x 204	320 x 280 x 201
Power Factor (PF)	> 95%			
CRI Ra	> 80%			
LED Lamp Life	30,000 hrs			
CCT K	65000K			
Input Voltage	220 - 240VAC , 50 - 60Hz			
Net Weight (Kg)	870g	1.2kg	4.1kg	4.7kg
Country of Origin	Korea			